

REFERENCES

- Abedi, S., and Buyamin, S. (2013). Sensorless Speed Estimation of Induction Motor Based on Feed-Forward Neural Network Algorithm. *IEEE Conference on Clean Energy and Technology (CEAT)*, 71–75.
- Agarwal, A., and Agarwal, V. (2012). FPGA realization of trapezoidal PWM for generalized frequency converter. *IEEE Transactions on Industrial Informatics*, 8(3): 501–510.
- Aiman, M., Azmi, M., Daniyal, H., and Bakar, M. S. (2014). Realization Of Three-Phase Voltage Source Inverter Controller Using ARM CORTEX-M3, *International Journal of Power Electronic Research Vol 2*: 1–5.
- Aroca, R. V., and Gonçalves, L. M. G. (2012). Towards green data centers: A comparison of x86 and ARM architectures power efficiency. *Journal of Parallel and Distributed Computing*, 72(12): 1770–1780.
- Asaei, B., and Rostami, A. (2009). A novel starting method for BLDC motors without the position sensors. *Journal of Energy Conversion and Management*, 50(2): 337–343.
- Bennett, T., Zilouchian, A., and Messenger, R. (2013). A proposed maximum power point tracking algorithm based on a new testing standard. *Solar Energy*, 89: 23–41.
- Boost, M. A., and Ziogas, P. D. (1988). State-of-the-Art Carrier Pwm Techniques: a Critical Evaluation. *IEEE Transactions on Industry Applications*, 24(2): 271–280.
- Buechley, L. (2010). LilyPad Arduino: rethinking the materials and cultures of educational technology. *Proceedings of the 9th International Conference of the Learning Sciences*, 2: 127–128.

- Chang, T.Y., Pan, C.T., and Fang, E. (2010). A Novel High Performance Variable Speed PM BLDC Motor Drive System. *Power and Energy Engineering Conference (APPEEC), 2010 Asia-Pacific*, (2): 1–6.
- Chudnovets, S. (2013). Novel structure of variable speed drive for ESP induction motor control. *2013 14th International Conference of Young Specialists on Micro/Nanotechnologies and Electron Devices*, 265–268.
- Clements, A. (1999). Selecting a processor for teaching computer architecture, *Microprocessors and Microsystems*, 23(5): 281–290.
- Depenbrock, M. (1988). Direct self-control (DSC) of inverter-fed induction machine. *IEEE Transactions on Power Electronics*, 3(4): 420–429.
- Gaballah, M., and El-Bardini, M. (2013). Low cost digital signal generation for driving space vector PWM inverter. *Ain Shams Engineering Journal*, 4(4): 763–774.
- Göddecke, D., Komatitsch, D., Geveler, M., Ribbrock, D., Rajovic, N., Puzovic, N., and Ramirez, A. (2013). Energy efficiency vs. performance of the numerical solution of PDEs: An application study on a low-power ARM-based cluster. *Journal of Computational Physics*, 237: 132–150.
- Iso, U., Control, F., Ic, T. W. I., Is, S. S. C., Sdio, H., and Mmc, S. D. (n.d.). AT91SAM ARM-based SAM3X SAM3X / A.
- Jayetileke, H. R., and Mel, W. R. De. (2014). Real-Time Fuzzy Logic Speed Tracking Controller for a DC Motor Using Arduino Due. *7th International Conference on Information and Automation for Sustainability*, 1-6.
- Jung, H., Chee, S., and Sul, S. (2012). Control of three phase inverter for AC motor drive with small DC-link capacitor fed by single phase AC source. (*Ecce*), *2012 Ieee*, 50(2): 1074–1081.

- Jung, S., Bae, Y., Choi, S., Member, S., and Kim, H. 2007. A Low Cost Utility Interactive Inverter for Residential Fuel Cell Generation, *IEEE Transactions on Power Electronics* 22(6): 2293–2298.
- Khlaief, A., Boussak, M., and Châari, A. (2014). A MRAS-based stator resistance and speed estimation for sensorless vector controlled IPMSM drive. *Electric Power Systems Research*, 108: 1–15.
- Kim, J., Ha, K., and Krishnan, R. (2012). Single-Controllable-Switch-Based Switched Reluctance Motor Drive for Low Cost. *Ieee Transactions on Power Electronics*, 27(1): 379–387.
- Kocman, S., and Orság, P. (2014). Efficiency Evaluation of Various Assemblies of Variable Speed Drive. *Environment and Electrical Engineering (EEEIC), 2014 14th International Conference on Krakow*, (1):360-364.
- Kumar, L., and Jain, S. (2014). Electric propulsion system for electric vehicular technology: A review. *Renewable and Sustainable Energy Reviews*, 29: 924–940.
- Liang, X., and Xu, W. (2013). Modeling variable frequency drive and motor systems in power systems dynamic studies. *IEEE Industry Applications Society Annual Meeting*, 1–11.
- Magzoub, M. a, and Ibrahim, R. B. (2013). Analysis and Modeling of Indirect Field-Oriented Control for PWM-driven Induction Motor Drives. *IEEE Conference on Clean Energy and Technology (CEAT)*, 488–493.
- Motor, M., and Drive, V. (2014). Effect of Coercive Force and Characteristics of a Pole Changing Permanent Magnet Motor for Variable-Speed Drive. *Power Electronics and Applications (EPE'14-ECCE Europe)*, 1-10.
- Moungkhum, N., and Subsingha, W. (2013). Voltage Control by DQ Frame Technique of SVPWM AC- DC Converter. *Energy Procedia*, 34: 341–350.

- Mounika, K., and Babu, B. K. (2013). Sinusoidal and Space Vector Pulse Width Modulation for Inverter. *International Journal of Engineering Trends and Technology (IJETT)* 4(4): 1012–1017.
- Mujumdar, U. B., and Tutkane, D. R. (2014). Selection of Digital Controller for Power System and Power Electronics Applications. *2014 International Conference on Electronic Systems, Signal Processing and Computing Technologies*, 84–88.
- Murthy, A. A., Rao, N., Beemaiah, Y. R., Shandilya, S. D., and Siddegowda, R. B. (2014). Design and Construction of Arduino-Hacked Variable Gating Distortion Pedal. *IEEE Access* 2: 1409–1417.
- Mwinyiwiwa, B., Wolanski, Z., and Ooi, B.-T. (1998). Microprocessor-Implemented SPWM for. *Ieee Transactions on Industry Applications*, 34(3): 487–494.
- Nathenas, T., and Adamidis, G. (2012). A new approach for SVPWM of a three-level inverter-induction motor fed-neutral point balancing algorithm. *Simulation Modelling Practice and Theory*, 29: 1–17.
- Nithyasree, M., and Kandasamy, K. V. (2012). A Generic PID Controller Based on ARM Processor. *Procedia Engineering*, 38: 1044–1049.
- Oxer, J., and Blemings, H. (2010). *Practical arduino: Cool projects for open source hardware*. Apress.
- Pena, R., Clare, J. C., and Asher, G. M. (1996). Doubly fed induction generator using back-to-back PWM converters and its application to variable-speed wind-energy generation. *IEE Proceedings - Electric Power Applications*, 143(3): 231.
- Persson, E. (1992). Transient effects in application of PWM inverters to induction motors. *IEEE Transactions on Industry Applications*, 28(5): 1095–1101.

- Pittini, R., and Andersen, M. A. E. (2013). An Interface Board for Developing Control Loops in Power Electronics Based on Microcontrollers and DSPs Cores – Arduino / ChipKit / dsPIC / DSP / TI Piccolo. *Control and Modeling for Power Electronics (COMPEL), 2013 IEEE 14th Workshop*, 1-7.
- Price for component (online). Retrieved from <http://www.cytron.com.my> and <http://www.element14.com> on 5 September 2015.
- Bowes, S. R. (1997). The Relationship Between Space-Vector Modulation. *IEEE Transactions on Industry Applications*, 44(5): 670–679.
- Qazalbash, A. A., Amin, A., Manan, A., and Khalid, M. (2009). Design and implementation of microcontroller based PWM technique for sine wave inverter. *2009 International Conference on Power Engineering, Energy and Electrical Drives*, 163–167.
- Rajovic, N., Rico, A., Puzovic, N., Adeniyi-Jones, C., and Ramirez, A. (2014). Tibidabo: Making the case for an ARM-based HPC system. *Future Generation Computer Systems*, 36: 322–334.
- Reddy, M. H. V., and Jegathesan, V. (2011). Open loop V/f control of induction motor based on hybrid PWM with reduced torque ripple. *2011 International Conference on Emerging Trends in Electrical and Computer Technology*, 331–336.
- Russell, L., Member, S., and Lukerussellcarletonca, E. (2012). Low-Cost , Rapid Prototyping of IMU and Pressure Monitoring System using an Open Source Hardware Design. *2012 IEEE International of Instrumentation and Measurement Technology Conference (I2MTC)*, 2695 - 2699.
- Saidur, R., Mekhilef, S., Ali, M. B., Safari, A., and Mohammed, H. A. (2012). Applications of variable speed drive (VSD) in electrical motors energy savings. *Renewable and Sustainable Energy Reviews*, 16(1): 543–550.

- Saragat, V. (2004). *Spectral aliasing effects of pwm signals with time-quantized deis*. Ph.D. Thesis. University of Bologna Viale Risorgimento 2 DI , University of Ferrara.
- Severance, C. (2014). Massimo banzi: Building arduino. *Computer*, 47(1): 11–12.
- Shireen, W., Vanapalli, S., and Nene, H. (2007). DSP based inverter control for alternate energy systems. *Journal of Power Sources*, 166(2): 445–449.
- Su, C., Member, S., Chung, W., and Yu, K. (2014). An Energy-Savings Evaluation Method for Variable-Frequency-Drive Applications on Ship Central Cooling Systems. *IEEE Transactions on Industry Applications* 50(2): 1286–1294.
- Sudhahar, R., and Jamuna, V. (2012). A Review of Pioneer Fiction Realization of Embedded Core FPGA Based Control of Single Phase to Three Phase SVPWM Converter for Electrical Drives. *Procedia Engineering*, 30(2011): 694–702.
- Swamy, M. M., and Collins, J. (2014). An Optimal Solution For Operating a Three-Phase Variable Frequency Drive From a Single-Phase AC Source. *2014 IEEE Energy Conversion Congress and Exposition (ECCE)*, 1699–1706.
- System, I. (2009). Power Considerations In FPGA Design (Technical Report).
- Tamminen, J., Ahonen, T., Kosonen, A., and Ahola, J. (2014.). Variable speed drive-based pressure optimization of a pumping system comprising individual branch flow control elements. *Power Electronics and Applications (EPE'14-ECCE Europe)*, 1-11.
- Thomson, W. T., and Fenger, M. (2001). Current signature analysis to detect induction motor faults. *IEEE Industry Applications Magazine*, 7(4): 26–34.
- Valan Rajkumar, M., and Manoharan, P. S. (2013). FPGA based multilevel cascaded inverters with SVPWM algorithm for photovoltaic system. *Solar Energy*, 87: 229–245.

- Valsan, S. P., Vaidya, T., and Chaudhary, M. (2011). Modified reference PWM for harmonic reduction in inverters. *India International Conference on Power Electronics 2010 (IICPE2010)*, 1–4.
- Yao-fei, H., Guo-jun, T., Hao, L., Zong-bin, Y., and Xuan-qin, W. (2009). Back-to-back three-level double-fed induction motor control system for mine hoist. *Procedia Earth and Planetary Science*, 1(1): 1448–1454.
- Yiu, J. (2014). *The Definitive Guide to Arm® Cortex®-M3 and Cortex®-M4 Processors*. Elsevier, Inc.
- Zhang, K., Kang, Y., Xiong, J., and Chen, J. (2003). Direct repetitive control of SPWM inverter for UPS purpose. *IEEE Transactions on Power Electronics*, 18(3): 784–792.
- Zulkifli, S. A. (2014). MATLAB-Arduino as a Low Cost Microcontroller for 3 phase inverter. *2014 IEEE Student Conference Research and Development (SCOReD)*, 1-5.